

Operator must visually inspect the hoisting apparatus daily in accordance with paragraph 211 (2) (a) of *General Regulation 91-191*.

Articulating Boom Crane

Indicate inspected items with a check Month: _____ Year: _____

Control Mechanism: Check for malfunction, control motion identification legibility, excessive wear and contamination.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Safety Devices: Check for malfunction.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Hydraulic Hoses: Check for evidence of leakage, especially at threaded or clamped joints. Check for blistering, abrasion, scrubbing or abnormal deformation to outer covering.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Hook and Latches: Check for deformation, cracks and wear.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Rope Reeving: Check wire rope for broken strands, bird caging or kinking. Ensure rope is spooled on drum evenly.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Hydraulic System: Check for leaks and proper oil levels.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Connecting Pins: Check for wear and damage.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Mounting Bolts: Check for evidence of loose or broken bolts.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Boom Sections: Check for cracks, broken welds and deformation.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

If other operators use the crane on any given day, they must indicate by signing that all of the above items have been inspected.

Operator 1																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 2																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 3																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Comments/Repairs	Initials	Date

Any document appearing in paper form is uncontrolled and must be compared to the electronic version.

Operator must visually inspect the hoisting apparatus daily in accordance with paragraph 211 (2) (a) of *General Regulation 91-191*.

Base-Mounted Drum Hoist (Tugger)

Indicate inspected items with a check Month: _____ Year: _____

Check all control mechanisms for malfunction.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check limit switches for malfunction.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check air or hydraulic systems for deterioration or leakage.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check load carrying ropes for excessive wear, kinking, or broken strands.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check electrical apparatus for malfunction.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check anchorage points and foundation for breakage.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Ensure guards are installed over exposed moving parts.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

If other operators use the hoist on any given day, they must indicate by signing that all of the above items have been inspected.

Operator 1																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 2																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 3																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Comments/Repairs	Initials	Date

Operator must visually inspect the hoisting apparatus daily in accordance with paragraph 211 (2) (a) of *General Regulation 91-191*.

Automotive Hoist

Indicate inspected items with a check Month: _____ Year: _____

Ensure warning labels, rated load capacity and safety tips are accessible and readable.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check operating controls, restraints and locking devices for malfunction.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check structural components for excessive wear or deformation.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check other components such as hoses, electrical wires, drive chains, cables and screws for excessive wear or deformation.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check contact points that engage vehicles during lifts for damage or excessive wear.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check for hydraulic or pneumatic leaks.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check hydraulic reservoirs for correct oil levels.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check for any unusual noise, sudden movements, erratic operation or evidence of chips or filings during use.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check for cracks or loose concrete around floor anchor bolts.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Check floor anchor bolts for evidence of looseness or breakage.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

If other operators use the hoist on any given day, they must indicate by signing that all of the above items have been inspected.

Operator 1																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 2																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 3																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Comments/Repairs	Initials	Date

Any document appearing in paper form is uncontrolled and must be compared to the electronic version.

Daily Visual Inspection

Operator must visually inspect the hoisting apparatus daily in accordance with paragraph 211 (2) (a) of *General Regulation 91-191*.

Hand-Operated / Level Operated Chain Hoist

Indicate inspected items with a check Month: _____ Year: _____

Hooks: Check Safety latches on both the support and lifting hooks for distortion or stretching.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Load Chain: Check for gross damage, kinks, and excessive wear. Load chain should not contain splices.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Support Structure: Check support structure for damage and security.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Motions: Ensure motions are smooth and regular with no hesitations, vibration, binding, unusual noise, or other irregularity.																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

If other operators use the hoist on any given day, they must indicate by signing that all of the above items have been inspected.

Operator 1																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 2																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Operator 3																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	

Comments/Repairs	Initials	Date

Operator must visually inspect the hoisting apparatus daily in accordance with paragraph 211 (2) (a) of *General Regulation 91-191*.

Electric / Pneumatic Hoists

Indicate inspected items with a check

Month: _____ Year: _____

Hoist Chains: Check for distortion, wear, stretching, nicks or deep gauges. Hoist chains should not contain splices. Contact the manufacturer to repair broken hoist chains.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Hoist Cable: Check for broken strands, bird caging and kinking. Ensure at least two wraps of cable on drum when hook is in lowest position.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Limit Switches: Check top and bottom switches for malfunction. Hoists operating on rails must have positive safe limit stops.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Hooks: Check safety latches on both the support and lifting hooks for any distortion or stretching.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Support Structure: Check support structure for cracks, bends or distortion.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

If other operators use the hoist on any given day, they must indicate by signing that all of the above items have been inspected.

Operator 1

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Operator 2

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Operator 3

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Comments/Repairs

Initials

Date

Comments/Repairs																														Initials	Date

Any document appearing in paper form is uncontrolled and must be compared to the electronic version.