

Safe Work Practice (SWP)

		Name of Task: Circular Saw		
Don	artment/Unit: 1	Fradas		
Deb				
		e Equipment or other required equipment or other safety considerations:		
	Eye protection required			
	No loose fitting clothing			
	CSA approved safety footwear required			
	Hearing protection required Approved Dust Mask if required dependent on material used - Confirm with Instructor or MSDS			
	•	shes, rings, necklaces, etc.		
	ards:	······································		
	Loose knots or f			
	Dust/debris irritation			
	Cuts, lacerations and amputations			
	Noise Draiactile work n	vience from improper elemping		
		 bieces from improper clamping Successful completion of NBCC Safety Course (Work Safety or Workplace) 		
Required Training		 Successful completion of NBCC Safety Course (Work Safely or Workplace Safety Practices) 		
		 Shop safety orientation Read and understand SWP 		
Pre	Operational	Inspect required personal protective equipment and replace if required.		
Safety Checks		 Ensure no slip/trip hazards are present in workspaces and walkways. Make sure guards, if present, are installed and are working properly. 		
		 Locate and ensure you are familiar with the operation of the ON/OFF starter. 		
Prohibited		 Do not leave this equipment running unattended 		
ACT	vities	Cutting irregular stock, branches or wood with embedded nails or screws		
		Steps to be taken to complete task safely:		
1	Wear appro	opriate personal protective equipment (PPE).		
2	Check the	Check the retracting lower blade guard frequently to make certain it works freely.		
3	Make all ac	Make all adjustments with power cord unplugged.		
4		Set the depth of the blade and lock it at a depth so that the lowest tooth does not extend more		
		t 6 mm (1/4 inch) beneath the wood. ock being cut to avoid movement.		
5 6		Keep all cords clear of cutting area.		
7		Circular saws are designed for right-hand operation; left-handed operation will demand more		
-	care to ope	perate safely.		
8	Use two ha	Use two hands to operate saws - one on a trigger switch and the other on a front knob handle.		
9	Allow the s	Allow the saw to reach full power before starting to cut.		
10		Allow it to cut steadily. Do not force it. Do not twist the saw to change, cut or check alignment.		
11	Keep moto	Keep motor free from accumulation of dust and chips.		
12	Turn saw C	Turn saw OFF and let blade come to a rest before removing work piece.		
13		Check that the retracting lower blade guard has returned to its starting position before laying down the saw.		
		Clean up dust and debris with POWER OFF		

Any document appearing in paper form is uncontrolled and must be compared to the electronic version.

If an emergency occurs while conducti the equipment off immediately and follo	ng this task, or there is an equipment malfunction, shut ow the lock out procedure.			
REPORT ANY HAZARDOUS SITUATION TO YOUR INSTRUCTOR/SUPERVISOR IMMEDIATELY				
Housekeeping				
	Switch off the machine and reset all guards to a fully closed position.			
	 Leave the machine in a safe, clean and tidy state. When servicing equipment (ex. changing a blade), power must be disconnected. 			
When servicing equipment (ex. cha	anging a blade), power must be disconnected.			
Responsibilities	s, Completion and Review			
regulations/guidelines, policies and procedures (e Procedures). Notify Manager or designates (i.e. supe	ormed in accordance to training, established health and safety .g. utilizing personal, protective equipment as per SAFE Work ervisors) of all occurrences, injuries illnesses or safety and health /es, co-workers, or any others who enter the premises.			
Completed by and Date: 1/20/2020	Approved by: Catherine Black – Dean, Trades			
Last Reviewed / Revised by and Date:	Note: This task will be monitored periodically to			